



Revision Number: 012.0

Issue date: 03/22/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE SI 5900 INSTANT GASKET known as Instant Gasket 90ml AE Product type: Silicone Sealant Restriction of Use: None identified Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	IDH number: 743912 Item number: 40478 Region: United States Contact information: Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com
--	---

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.
 CAUSES SKIN IRRITATION.
 MAY CAUSE AN ALLERGIC SKIN REACTION.
 CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
GASES UNDER PRESSURE	Compr. Gas
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention:	Avoid breathing mist or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Protect from sunlight. Store in a well-ventilated place.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Calcium carbonate	471-34-1	30 - 40
Siloxanes and Silicones, di-Me	63148-62-9	10 - 20
Norflurane	811-97-2	5 - 10
Butan-2-one O,O',O''-(vinylsilyldiene)trioxime	2224-33-1	1 - 5
Octadecanoic acid	57-11-4	1 - 5
Carbon black	1333-86-4	0.1 - 1
Aluminum	7429-90-5	0.1 - 1
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime	34206-40-1	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Wipe off paste with paper towel or cloth. Wash with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
Ingestion:	Do not induce vomiting. Seek medical advice.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Use water spray to keep fire exposed containers cool and disperse vapors.
Unusual fire or explosion hazards:	Contents under pressure. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of Silicon Oxides of carbon. Formaldehyde

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow spill to enter sewage systems or open bodies of water.
Clean-up methods:	Maintain good ventilation for large spills. Scrape up as much material as possible. Place scrap material in a well ventilated area and allow to cure to rubber.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation.

Storage: Store in a cool, dry, well-ventilated area.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Calcium carbonate	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Siloxanes and Silicones, di-Me	None	None	None	None
Norflurane	None	None	1,000 ppm (4,240 mg/m3) TWA	None
Butan-2-one O,O',O''-(vinylsilyldiene)trioxime	None	None	None	None
Octadecanoic acid	10 mg/m3 TWA	None	None	None
Carbon black	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL	None	None
Aluminum	1 mg/m3 TWA Respirable fraction.	15 mg/m3 PEL (as Al) Total dust. 5 mg/m3 PEL (as Al) Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Aerosol
Color: Black
Odor: Mild, Petroleum
Odor threshold: Not available.
pH: Not available.
Vapor pressure: Not available.

Boiling point/range:	Not available.
Melting point/ range:	Not available.
Vapor density:	Not available.
Flash point:	> 93.00 °C (> 199.4 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Polymerizes on contact with water.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	3.90 %; 50.70 g/l
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur
Hazardous decomposition products:	Oxides of carbon. Oxides of silicon. Methyl ethyl ketoxime formed during cure. Formaldehyde.
Incompatible materials:	Polymerizes on contact with water.
Reactivity:	Not available.
Conditions to avoid:	Moisture.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	Inhalation of mist or spray may cause irritation of the respiratory tract and nasal passages. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	Not expected under normal conditions of use. May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Calcium carbonate	Oral LD50 (Rat) = 6,450 mg/kg Oral LD50 (Mouse) = 6,450 mg/kg	Nuisance dust
Siloxanes and Silicones, di-Me	None	Irritant
Norflurane	None	Cardiac, Central nervous system, Irritant, Respiratory, Skin
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime	None	Irritant, Allergen
Octadecanoic acid	Oral LD50 (Rat) = 4.6 g/kg	Irritant
Carbon black	Oral LD50 (Rat) = > 8,000 mg/kg	Respiratory, Some evidence of carcinogenicity
Aluminum	None	Central nervous system, Irritant, Lung
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime	None	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Calcium carbonate	No	No	No
Siloxanes and Silicones, di-Me	No	No	No
Norflurane	No	No	No
Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime	No	No	No
Octadecanoic acid	No	No	No
Carbon black	No	Group 2B	No
Aluminum	No	No	No
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols
Hazard class or division: 2.2
Identification number: UN 1950
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, non-flammable
Hazard class or division: 2.2
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS
Hazard class or division: 2.2
Identification number: UN 1950
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

Issue date: 03/22/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.